



Data sheet – Gas Regulator

Multi-Flow



Type	Variable Flow										
Inlet	C10 (5/8" UNF M)										
Outlet	1/4" Hose Barb										
Available Flow Rates	<table border="1"> <tr> <td>0,0 l/min.</td> <td>2,0 l/min.</td> </tr> <tr> <td>0,5 l/min.</td> <td>2,5 l/min.</td> </tr> <tr> <td>0,75 l/min.</td> <td>3,0 l/min.</td> </tr> <tr> <td>1,0 l/min.</td> <td>4,0 l/min.</td> </tr> <tr> <td>1,5 l/min.</td> <td>5,0 l/min.</td> </tr> </table>	0,0 l/min.	2,0 l/min.	0,5 l/min.	2,5 l/min.	0,75 l/min.	3,0 l/min.	1,0 l/min.	4,0 l/min.	1,5 l/min.	5,0 l/min.
0,0 l/min.	2,0 l/min.										
0,5 l/min.	2,5 l/min.										
0,75 l/min.	3,0 l/min.										
1,0 l/min.	4,0 l/min.										
1,5 l/min.	5,0 l/min.										
Available Body Materials	Nickel Plated Brass or Stainless Steel										
Gauge	70 bar / 1000 psi										
Cylinder Type	34 Ltr / 60 Ltr. / 110 Ltr.										

Material-No.	Flow Rate	Body Material
1152105111	0 – 5,0 l/min.	Nickel Plated Brass
1122105111	0 – 5,0 l/min.	Stainless Steel

